

A.S.M.E. Certified Moisture Separators

1

TX-1MS



TX-2MS



Texas Pneumatic proudly introduces this line of moisture separators. These units are designed to work with one tool or in conjunction with our manifolds as seen below. The internal baffle is designed to eliminate 99% of the entrained water in the compressed air line. Its portability allows the user to position it as close to the work area and as far from the compressor as possible. The drain should be kept open to continually flush the condensation from the air line. Both size tanks are A.S.M.E. coded for OSHA compliance and safety. No long term maintenance is required.

| SPECIFICATIONS | |
|---------------------|---------|
| MODEL # | TX-1MS |
| WEIGHT | 29 lbs |
| HEIGHT | 11.5" |
| LENGTH | 22" |
| MINIMUM FLOW RATE | 24 cfm |
| MAXIMUM FLOW RATE | 330 cfm |
| INLET / OUTLET SIZE | 1" |

| SPECIFICATIONS | |
|---------------------|----------|
| MODEL # | TX-2MS |
| WEIGHT | 58 lbs |
| HEIGHT | 14.5" |
| LENGTH | 28" |
| MINIMUM FLOW RATE | 175 cfm |
| MAXIMUM FLOW RATE | 1300 cfm |
| INLET / OUTLET SIZE | 2" |

